

SLAT -BUILD YOUR SPECIFICATION

Complete the table and use the details in your project specification.

PRODUCT	SLAT	SUPPLIER	DECOR SYSTEMS - PH: 1800 835 035	
PROFILE	(CHOOSE A PROFILE FROM THE LIST ABOVE)			
FINISH	SOLID TIMBER	2 PACK POLY PAINT	SMARTLOOK LAMINATE	NATURAL TIMBER VENEER
FINISH VARIATION	(E.G. AMERICAN OAK)			
SUBSTRATE	(CHOOSE A SUBSTRATE FROM THE LIST ABOVE)			
FIXING METHOD	(CHOOSE A FIXING METHOD FROM THE LIST ABOVE)			
BACKING	ACOUSTIC PANEL	SOLID BACKING	CROSS BATTEN (NB* SOLID BACKING IS FOR DECORATIVE PURPOSES ONLY. CROSS BATTENS FOR AN OPEN BACKING.)	
FIRE CERTIFICATION	SLAT COMES WITH A GROUP 3 FIRE RATING. IT CAN ACHIEVE A GROUP 2 OR IN SOME CASES A GROUP 1 CERTIFICATION WHEN A SPECIFIC COMBINATION OF SUBSTRATE AND FINISH IS USED. PLEASE DISCUSS THIS WITH YOUR DECOR SYSTEMS PROJECT CONSULTANT.			
NOTES	(ANY EXTRA INFORMATION YOU WOULD LIKE TO ADD?)			
<p>This product requires an air gap and DecorInsul behind the panels for the best acoustic performance. Consult the acoustic test results, and opinion of project acoustic engineer for more details. If not available due to site constraints or budget, a 50mm gap with DecorInsul works in most cases.</p> <p>Close collaboration between Decor Systems, the project architect and the client has taken place to develop this specification. Slat cannot be substituted unless agreed by Architect and Acoustic Engineer.</p> <p>Panels should be allowed to acclimatise on site for at least five days before installation. Decor Systems certificate # (Contact your Decor Systems project consultant for your individual project number) to be supplied upon completion.</p> <p>Panel installation to be as per manufacturer's instructions and AS/NZS 2785. - Installation to be done by an approved ceiling and partition contractor.</p> <p>Product guarantee to be 99 years as per Decor Systems guarantee. Please contact Decor Systems for your project specific completion number.</p>				