

Certification Body:

global-mark

Global-Mark Pty Ltd,

Suite 4.07. 32 Delhi Road, North Ryde NSW 2113, Australia Ph: +61 2 9886 0222 global-mark.com.au

Type and/or use of product:

VITRADUAL panels are used in external wall cladding, in all building types (NCC Volume 1 & 2)

G5D4

Volume One

Certificate number: CM30017 Rev 2

THIS IS TO CERTIFY THAT

VITRADUAL

Description of product:

VITRADUAL panels are 3 mm thick PVDF coil coated solid Aluminium panels installed with metal fixing system. Standard panel sizes include widths of 1,250mm & 1,500m and lengths of 2,500mm, 3,200mm & 4,000mm. Custom panel sizes up to 1,500mm x 4,000mm.

Volume Two and Housing Provisions (HP)

COMPLIES WITH THE FOLLOWING BCA PROVISIONS AND STATE OR TERRITORY VARIATION(S)

BCA 2022

B1P1 Performance Requirement(s) Structural Provisions **H1P1** Structural stability and resistance to actions **Certificate Holder:** B1P2 Structural Provisions **FVA Group Pty Ltd** F3P1 Damp and Weatherproofing H2P2

Weatherproofing 18-20 Donald St Lithgow NSW 2790 Deemed-to-Satisfy Provision(s): B1D4 (e) Structural Resistance HP 2.2.4 (k) Structural Resistance Ph: +61 2 6352 2355 C2D10 (6)(e) Non-Combustible Material www.fv.com.au

G5D3 Construction in bushfire prone areas H7D4 (2)(a) Construction in bushfire prone areas Protection - residential buildings Construction in bushfire prone areas

Scope of certification: The CodeMark Scheme is a building product certification scheme. The rules of the Scheme are available at the ABCB website www.abcb.gov.au. This Certificate of Conformity is to confirm that the relevant requirements of the Building Code of Australia (BCA) as claimed against have been met. The responsibility for the product performance and its fitness for the intended use remain with the certificate holder. The certification is not transferrable to a manufacturer not listed on Appendix A of this certificate.

Protection – certain Class 9 buildings

Disclaimer: The Scheme Owner, Scheme Administrator and Scheme Accreditation Body do not make any representations, warranties or guarantees, and accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of any material contained within this certificate; and the Scheme Owner, Scheme Administrator and Scheme Accreditation Body disclaim to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this certificate. The purpose of Global-Mark construction site audits is to confirm the practicability of installing the product; and to confirm the appropriateness and accuracy of installation instructions

In placing the CodeMark mark on the product/system, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. In issuing this Certificate of Approval Global-Mark has relied on the expertise of external bodies (laboratories, and technical experts).

Herve Michoux **Global-Mark Managing Director**

Certificate number: CM30017 Rev 2

Peter Gardner **Unrestricted Building Certifier**

V. Gardwir

Date of expiry: 29/06/2026





Date of issue: 29/06/2023



State or territor	y variation(s): NT B1D4 (e) QLD B1D4 (e) WA B1D4 (e)	Structural Resistance	WA 2.2.4 (k)	Structural Resista	nce	
	NSW G5D3 NSW G5D4 VIC G5D4 SA G5D5	Bushfire: Protection – residential buildings Bushfire: Protection – certain Class 9 buildings Bushfire: Protection – certain Class 9 buildings Bushfire attack levels	NSW H7D4 (2)(a) QLD H7D4 (3) SA H7D4 (3)	Construction in b	ushfire prone areas ushfire prone areas ushfire prone areas	
SUBJEC	SUBJECT TO THE FOLLOWING LIMITATIONS AND CONDITIONS AND THE PRODUCT TECHNICAL DATA IN APPENDIX A AND EVALUATION STATEMENTS IN APPENDIX B					
Limitations and	conditions:				Building classification/s:	
Wind load limits Supporting struc	Vitradual panel system as described has maximum design wind load limits documented within the Vitradual Technical Manual, dated March 2020. Wind load limits, construction detail and fixing must follow the relevant details contained within the Vitradual Technical Manual, dated March 2020. Supporting structures & connections (including stud frame & sub framing members) must be designed / specified to withstand project loads including out not limited to ULS & SLS wind loads.					
Volume 1 – B1P Snow, liquid pre	1 (2) (e), (f) & (i) & Vo ssure and earth pressure actions ar	olume 2 – H1P1 (2) (e), (f) & (i) e excluded.			1, 2, 3, 4, 5, 6, 7, 8, 9 & 10	
Volume 1 – B1P Compliance for	4 & Vo	olume 2 – H1P2			1, 2, 3, 4, 5, 6, 7, 8, 9 & 10	
 the Flexib When a Fl When a R Design & Design ac Installatio Fixings are 	rnal wall must be constructed using le Wall Wrap or Rigid Air Barrier mu exible wall wrap (Water Barrier) is gid Air Barrier is used for a wall wrap stallation complies fully with Vitra commodates deflection movements in Contractor complies with manufa	either a pliable building membrane or Rigid Air Barrier, so ist present an Air & Water barrier for the purposes of weat used, the system remains weatherproof up to Serviceability, the system remains weatherproof up to Serviceability dual Technical Manual, dated March 2020, and so due to all design loads & temperature variations, and currer's instructions for sealants, shop drawings & project facturer's instructions & procedures, fixings to be weather	atherproofing, and ity wind loads of +1.5 kF wind loads of +3.5 kPa at specifications, and	Pa & -1.8 kPa, and & -4.0 kPa, and	1, 2, 3, 4, 5, 6 & 9	



Certificate number: CM30017 Rev 2

Certificate of Conformity

Volume 1 - C2D10 This Certification is based upon the system being installed using components & accessories specified in the "System Components" section of the Vitradual Technical Manual, dated March 2020 & the Vitrafix Accessories Brochure dated March 2020 (refer Appendix B2). Substitution of such components & / or accessories may be permitted, however the general performance specifications of components & / or accessories must be maintained for this certificate to remain valid. Volume 1 - C2D10 (1) In a building required to be of Type A or B construction, construction elements and their components must be non-combustible for all external walls, common walls and non-loadbearing internal walls that are required to be fire-resisting. This includes the requirement for Rigid Air Barriers to be non-combustible, where used. Volume 1 - C2D10 (6) Pliable building membranes / "Sarking-type materials" must not exceed 1mm in thickness and must have a Flammability index not greater than 5. Volume 1 - G5D3 & Volume 2 - H7D4 (2)(a) In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 - NSW G5D3 & Volume 2 - NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is p	2, 3, 4, 5, 6, 7, 8 & 9
This Certification is based upon the system being installed using components & accessories specified in the "System Components" section of the Vitradual Technical Manual, dated March 2020 & the Vitrafix Accessories Brochure dated March 2020 (refer Appendix B2). Substitution of such components & / or accessories may be permitted, however the general performance specifications of components & / or accessories must be maintained for this certificate to remain valid. Volume 1 – C2D10 (1) In a building required to be of Type A or B construction, construction elements and their components must be non-combustible for all external walls, common walls and non-loadbearing internal walls that are required to be fire-resisting. This includes the requirement for Rigid Air Barriers to be non-combustible, where used. Volume 1 – C2D10 (6) Pliable building membranes / "Sarking-type materials" must not exceed 1mm in thickness and must have a Flammability index not greater than 5. Volume 1 – G5D3 & Volume 2 – H7D4 (2)(a) In designated bushfire prone areas, when the buildings is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, vitradual is permitted for use as external wall cladding.	2, 3, 4, 5, 6, 7, 8 & 9
Vitradual Technical Manual, dated March 2020 & the Vitrafix Accessories Brochure dated March 2020 (refer Appendix B2). Substitution of such components & / or accessories may be permitted, however the general performance specifications of components & / or accessories must be maintained for this certificate to remain valid. Volume 1 – C2D10 (1) In a building required to be of Type A or B construction, construction elements and their components must be non-combustible for all external walls, common walls and non-loadbearing internal walls that are required to be fire-resisting. This includes the requirement for Rigid Air Barriers to be non-combustible, where used. Volume 1 – C2D10 (6) Pliable building membranes / "Sarking-type materials" must not exceed 1mm in thickness and must have a Flammability index not greater than 5. Volume 1 – G5D3 & Volume 2 – H7D4 (2)(a) In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	
In a building required to be of Type A or B construction, construction elements and their components must be non-combustible for all external walls, common walls and non-loadbearing internal walls that are required to be fire-resisting. This includes the requirement for Rigid Air Barriers to be non-combustible, where used. Volume 1 – C2D10 (6) Pliable building membranes / "Sarking-type materials" must not exceed 1mm in thickness and must have a Flammability index not greater than 5. Volume 1 – G5D3 & Volume 2 – H7D4 (2)(a) In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	
common walls and non-loadbearing internal walls that are required to be fire-resisting. This includes the requirement for Rigid Air Barriers to be non-combustible, where used. Volume 1 – C2D10 (6) Pliable building membranes / "Sarking-type materials" must not exceed 1mm in thickness and must have a Flammability index not greater than 5. Volume 1 – G5D3 & Volume 2 – H7D4 (2)(a) In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	2, 3, 4, 5, 6, 7, 8 & 9
Pliable building membranes / "Sarking-type materials" must not exceed 1mm in thickness and must have a Flammability index not greater than 5. Volume 1 – G5D3 & Volume 2 – H7D4 (2)(a) In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	
Volume 1 – G5D3 & Volume 2 – H7D4 (2)(a) In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	2, 3, 4, 5, 6, 7, 8 & 9
In designated bushfire prone areas, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, Vitradual is permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	
permitted for use as external wall cladding only in buildings subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19. In Queensland (per QLD G5D2 & QLD H7D4(3)), areas where the classified vegetation is Group F rainforest (excluding wet sclerophyll forest types), mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	1, 2, 3 & 10a or deck
mangrove communities and grasslands under 300mm high, are excluded. Volume 1 – NSW G5D3 & Volume 2 – NSW H7D4 In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	immediately adjacent or connected to building class 1,
In designated bushfire prone areas, subject to Bushfire Attack Level BAL-Low, BAL-12.5 & BAL-19, determined in accordance with the Planning for Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	or 3
Bush Fire Protection, when the building is constructed in accordance with AS3959: 2018 including Amendments 1 & 2, except as modified by Planning for Bush Fire Protection, Vitradual is permitted for use as external wall cladding.	1, 2, 3, Class 4 part of a
The compliance assessment of the certified system is limited to sections 7.5 and 8.3.2 of Planning for Bush Fire Protection.	building & 10a building or do immediately adjacent or connected to building of class
,	1, 2, 3 or Class 4 part of a building
Site specific conditions arising from:	U U
 the development consent following consultation with the NSW Rural Fire Service under section 4.14 of the Environmental Planning and Assessment Act 1979 if required, or 	
 the development consent with a bushfire safety authority issued under section 100B of the Rural Fires Act 1997 for the purposes of integrated development 	
have not been considered for the compliance assessment.	



Volume 1 – NSW G5D4	Class 9 building that is a	
In designated bushfire prone areas subject to a Bushfire Attack Level (BAL) not exceeding BAL—12.5, determined in accordance with Planning for Bush Fire Protection, when the building is constructed in accordance with:	special fire protection purpose; and a Class 10a	
1) For class 9 buildings, Specification 43 except as modified by Planning for Bush Fire Protection, or	building or deck immediately adjacent or connected to such	
2) For class 10a buildings or decks, AS3959: 2018 including Amendments 1 & 2 except as modified by Planning for Bush Fire Protection and S43C13,	building	
Vitradual is permitted for use as external wall cladding.		
The compliance assessment of the certified system is limited to sections 7.5 and 8.3.2 of Planning for Bush Fire Protection.		
Site specific conditions arising from the development consent with a bushfire safety authority issued under section 100B of the Rural Fires Act 1997 for the purposes of integrated development are site specific and have not been considered for the compliance assessment.		
General	1, 2, 3, 4, 5, 6, 7, 8, 9 & 10	
The supporting structures including stud frame & cavity sub framing, plus internal linings shall be designed & specified by a suitably qualified design professional in accordance with manufacturer guidelines. Installation shall be conducted by suitably qualified and trained building professionals. Design, Specification an Installation shall be in accordance with the Vitradual Technical Manual, dated March 2020 (refer Appendix B2).		



APPENDIX A - PRODUCT TECHNICAL DATA

A1 Type and intended use of product

Refer to page 1 of this certificate.

A2 Description of product

Refer to page 1 of this certificate.

This product is NOT an Aluminium Composite Panel (ACP).

A3 Product specification

Refer to items 1 & 2 listed in Appendix B2:

- VITRADUAL Technical Manual, dated March 2020.
- VITRAFIX Accessories Brochure, dated March 2020.

A4 Manufacturer and manufacturing plant(s)

FVA Group Pty Ltd

18-20 Donald Street

Lithgow NSW 2790

Ph: + 61 2 6352 2355

www.fv.com.au

A5 Installation requirements

Refer to items listed in Appendix B2:

- VITRADUAL Technical Manual, dated March 2020.
- VITRAFIX Accessories Brochure, dated March 2020.

A6 Other relevant technical data

Refer to items listed in Appendix B2:

- VITRADUAL Technical Manual, dated March 2020.
- VITRAFIX Accessories Brochure, dated March 2020.
- Any referenced documents within the above listed technical literature.



APPENDIX B – EVALUATION STATEMENTS

B1 Evaluation methods

The following assessment methods have been used to determine compliance with BCA 2022

Code Clause		Assessment Method(s)	Evidence of suitability	Evidence reference in B2
BCA Volume One	B1P1	A2G2 (2) (a), (b)(ii) & (c)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
BCA Volume Two	H1P1	A2G2 (2) (a), (b)(ii) & (c)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
BCA Volume One	B1P2	A2G2 (2) (a), (b)(ii) & (c)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
BCA Volume One	F3P1	A2G2 (2) (a), (b)(i) & (c)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 10, 11, 12 & 13
BCA Volume Two	H2P2	A2G2 (2) (a), (b)(i) & (c)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 10, 11, 12 & 13
BCA Volume One	B1D4 (e)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
BCA Housing Provisi	ions 2.2.4 (k)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
BCA Volume One	C2D10 (6)(e)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
BCA Volume One	G5D3	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
BCA Volume One	G5D4	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
BCA Volume Two	H7D4 (2)(a)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
BCA Volume One	NT B1D4 (e)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
	QLD B1D4 (e)			
	WA B1D4 (e)			
BCA Housing Provisi	ions WA 2.2.4 (k)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 1, 2, 3, 4 & 5
BCA Volume One	NSW G5D3	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
BCA Volume One	NSW G5D4	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
	VIC G5D4			
BCA Volume One	SA G5D5	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
BCA Volume Two	NSW H7D4 (2)(a)	A2G3 (2) (a) & (b)	A5G3 (1) (d) & (e) – Test Report & Expert Judgement	Items 6, 7, 8 & 9
	QLD H7D4 (3)			
	SA H7D4 (3)			



B2 Reports

The following reports have been used as evidence to determine compliance with BCA 2022:

Ref	Author	Reference	erence Date / Revision		NATA Registration	
1.	Fairview	iew VitraDual – Technical Information		Product Technical Manual	-	
2.	Fairview	VitraFix – Accessories Brochure	March 2020	Accessories Brochure	-	
3.	Enertren	ertren FAR-106 Vitradual Structural Design		Structural Assessment Report	-	
4.	Enertren	FAR-092 Span Tables	23 January 2019	Structural Span Tables	-	
5.	SGS Australia	N-0519-0921	25 October 2019	Material Investigation Report	-	
6.	CSIRO	FNC 11690	16 August 2016	Fire Test Report	165	
7.	AWTA	16-002875	7 June 2016	Fire Test Report	1356	
8.	Red Fire Engineers	JV19-00103-v2	27 March 2020	Fire Assessment Report	-	
9.	Exova WarringtonFire UK	WF 400695v2	5 June 2018	Fire Classification Report	UKAS 0249	
10.	BG&E Facades	FVA Cladding Products - VitraDual	27 August 2018	Weather tightness assessment report	-	
11.	FacadeLab NZ	18-02	20 April 2018	Weather tightness test report	IANZ 1091	
12.	VIPAC Engineers	30B-19-0059-TRP-6774697-1	1 April 2020	Weather tightness test report	676	
13.	VIPAC Engineers	30B-19-0059-TRP-6774698-0	2 April 2020	Weather tightness test report	676	

The Certificate Holder has chosen not to make the above identified evidence of compliance publicly available, due to the documents being considered commercial in confidence.

End of Certificate.