



The clever move

LINAK has the widest product programme on the market. We develop and provide solutions where all components work together. True systems where everything fits, it is simply Plug & Play.With our DESKLINE® systems you can concentrate on design, stability and furniture aesthetics. As a global leader we provide Plug & Play electric height adjustable solutions for desks, tables, counters and workstations which people work behind every day.



PVC-free systems

LINAK has acknowledged that there are alternatives to materials containing PVC. For health reasons and for the sake of the environment most DESKLINE systems are PVC-free as standard. Look for the PVC-free icon to denote products that are PVC-free.



ZERO™ technology

The environment is increasingly on people's minds. LINAK uses ZERO technology to lower standby power consumption to just 0.1W. All our DESKLINE control boxes have low standby power as standard. Look for the ZERO icon to denote products that have low standby power consumption.



PIEZO™ anti-collision technology

PIEZO is the name given to LINAK hardware based anti-collision technology. This feature prevents material damage to a desk if a collision with a solid object occurs. The PIEZO sensor is completely integrated in the column with no visible changes and no extra mounting. The PIEZO sensor is more sensitive and reacts faster than known software based systems. Look for the PIEZO logo to denote which DESKLINE columns offer PIEZO as a feature.





Power to the system









CBD4

- ZERO™ standby power consumption
- High performance, low pleasant sound and constant speed of the system
- Plug & Play with all lifting columns
- Up to 4 channels in parallel

- Compact, lightweight
 ZERO™ standby power consumption
- PVC-free as standard
- Intuitive cable management
- High performance, low pleasant sound and constant speed of the system
- Plug & Play with all lifting columns
- Up to 4 channels in parallel
- Universal input (300W)

BA001 Battery box

- Battery alarm (audio)
- Battery charging indicator (LED light bars)
- Capacity 2.2 Ah/53Wh
- Nominal voltage 24V
- Mounting bracket for easy mounting/demounting

CBD6S, a compact, state-of-the-art control box

The series of control boxes CBD6S combines the best of the past with new unique features into compact, state-of-theart control boxes. The CBD6S is backwards compatible and works with the entire DESKLINE® product programme. Weighing down to 400 g and with a height of only 38 mm it is easy to mount, and it has grooves in the bottom for intuitive cable management. Moreover, it is PVC-free and comes with ZERO standby power as standard.





300W











Movement of the desk

Throughout the years LINAK has launched a wide range of motor systems for office desks, tables, counters, workstations and kitchens.

All members of our DESKLINE® column family contribute to reliable, easy and innovative solutions for electric ergonomic adjustment to your desks. LINAK solutions focus on complete flexible systems based on your needs and wishes - both functionally and aesthetically.



LA31

Speed: 20 mm/sec.
Max thrust: 3500 N/leg
Stroke length: 500 mm

Available in several lengths

Baselift

Speed: 14 mm/sec. Max thrust: 1500 N Stroke length: 100 mm Built-in dim: 100 mm



DL1A

Speed: 43 mm/sec.
Max thrust: 1600 N/leg
Stroke length: 500 mm
Built-in dim.: 645 mm

Available in several lengths

DL5

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 500 mm
Built-in dim: 645 mm

Also available as a built-in actuator

DL6

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 650 mm
Built-in dim: 560 mm

Also available as a built-in actuator

Also available in a 1200N version DL7 and DL7R

Speed: 34 mm/sec.
Max thrust: 800 N/leg
Stroke length: 470 mm
Built-in dim: 645 mm

DL8

Speed: Max thrust: Stroke length: Built-in dim:

38 mm/sec. 800 N/leg 500 mm 645 mm





DL2

Speed: 20 mm/sec.
Max thrust: 2500 N/leg
Stroke length: 500 mm
Built-in dim: 645 mm

Available in several lengths

DL4

Speed: 43 mm/sec.
Max thrust: 700 N/leg
Stroke length: 675 mm
Built-in dim: 560 mm

Also available as a built-in actuator

DL12

 Speed:
 38 mm/sec.

 Max thrust:
 700 N/leg

 Stroke length:
 660 mm

 Built-in dim:
 518 or 545 mm

Also available as a built-in actuator

DL14

Speed: 38 mm/sec.
Max thrust: 700 N/leg
Stroke length: 660 mm
Built-in dim: 525 mm

Also available as a built-in actuator

DL17

Speed: 38 mm/sec.
Max thrust: 700 N/leg
Stroke length: 660 mm
Built-in dim: 518 mm

PVC FREE PVC









DL9

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 650 mm
Built-in dim: 560 mm

Also available in an XL-version

DL10

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 500 mm
Built-in dim: 645 mm

DL11

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 650 mm
Built-in dim: 560 mm

Also available in an XL-version

DL15

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 500 mm
Built-in dim: 645 mm

DL16

Speed: 38 mm/sec.
Max thrust: 800 N/leg
Stroke length: 650 mm
Built-in dim: 560 mm



Raise your control level

We have what you need. LINAK offers a full range of control units, in basic, advanced and wireless versions, with memory functions and displays monitoring the desk height and other data. The range of DESKLINE controls also includes motivational software and wellness switches.









- Small, compact panelUp-down function
- Intuitive use
- Adjustable front

- Small, compact panelUp-down function
- Intuitive use
- Fixed, angled front
- Drawer for easy mounting











DPF • Modern design

- Intuitive use
- Up-down function with optional memory buttons
- Separate mounting bracket

DPF1C

- Modern design
- Intuitive use
- Memory buttons
- Display for height read-outSeparate mounting bracket

DPF4T

PVC FREE

- Modern design
- Intuitive use
- · Memory buttons controlling up to 4 references
- Display for height read-out
- Separate mounting bracket











DPH

- Small, compact panelUp-down function
- For integration in tabletops
- Can be customised
- Available in black or white

DPT

- For integration in tabletopsTouch techniqueDisplay for height read-out

- Memory buttons Available in black or white

DP

- Classic controlUp-down function with optional memory buttons
- For parallel systems or for individual

DP1C

- Classic controlMemory buttonsDisplay for height read-out





PVC FREE



- HB10RF • Wireless handset (RF based)
- Easily operated
- Ergonomic design Available in 1 or 2 channel versions

DPF1W

- Modern design
- Display for height read-out
- Counts standing minutes and calories Report: tracks desk use
- Alarm: reminds the user to standSeparate mounting bracket



- A software desk panel
- Adjustment via PC or Mac
- Counts standing minutes and calories
- Report: tracks desk use
- Alarm: reminds the user to stand Customised user interface (option)





LINAK has a well-developed sales and service organisation in Europe, Americas, Asia and Australia. Therefore, we can assist you and your customers locally, under the global sales concept idea: Be global, act local



For further information about the DESKLINE® product programme: www.linak.com/deskline



Subscribe to LINAK DESKLINE news: www.linak.com/subscribe

Need support? Find answers to common questions about your DESKLINE motor system.



DESKLINE Support



Support videos at YouTube



DESKLINE user manuals

Terms of use

The user is responsible for determining the suitability of LINAK products for a specific application. LINAK takes great care in providing accurate and up-to-date information on its products. However, due to continuous development in order to improve its products, LINAK products are subject to frequent modifications and changes without prior notice. Therefore, LINAK cannot guarantee the correct and actual status of said information on its products. While LINAK uses its best efforts to fulfill orders, LINAK cannot, for the same reasons as mentioned above, guarantee the availability of any particular product. Therefore, LINAK reserves the right to discontinue the sale of any product displayed on its website or listed in its catalogues or other written material drawn up by LINAK.

