

LEDFLOOD



Type/Item No: LEDF100

Features:

- Die-cast aluminium alloy body
- Adjustable trunnion mounting bracket
- Stainless steel fixings
- Tempered clear glass(5mm)
- Silicone rubber seals
- Stainless steel cable gland
- Includes 1 x100w LED with 700mA Led driver
- 6500K colour temperature
- 240v direct connection
- Wide Beam Angle 120Deg
- Energy efficient alternative to halogen
- Low operating Temperature
- Less carbon emissions
- 50,000 hours
- No ultraviolet emissions
- 12 month warranty
- Weight 7.2Kg



Class:	IP	Colour:
1	IP65	Grey

Lamp:

1 x100w 700mA single chip LED

Gear:

Integral within housing at rear

COMPLIANCES:

Magnetic Emission	EN55015
Harmonic	EN61000-3-2
Flicker	EN61000-3-3
Immunity	EN61547
Safety	EN61347-1
Tested to IEC	61347-2-13(LED control gear)

Dimensions:

LED Performance

Luminous Flux	6300lm
Luminous Efficacy	60lm/w
Input Power	105w
Colour temperature	6500K
CRI	60Ra

Application:

Floodlighting and wall washing for Bars, Clubs, Hotels, Stages, Parks, Plaza, Commercial building façade, Domestic backyards, Parking Bays, Security areas, Walkways.

