

 **BASF**

The Chemical Company

Mastertop[®]

Floor Levelling





Floor Levelling

BASF Construction Chemicals has a complete range of floor levelling products for the floor coverings industry.

Mastertop® floor levelling products are the result of over 50 years of research and development by our sister company PCI Augsburg GmbH, the market leader in hard floor underlays and adhesives in Germany.

The BASF floor levelling range is suitable for carpet, vinyl, tiles, parquet and timber floors. The range also includes an overlay suitable for foot traffic, cars and other rubber-wheeled equipment.





Mastertop® Floor Levelling Range

Mastertop® P-5

Fine finishing material for filling minor divots, smoothing out ridges and feather-edging. Rapid setting formulation allows for fast installation of floor coverings.

Available in 4.5kg bags.

Mastertop® P-8

An economical self-levelling floor underlayment. Suitable for over poured insitu and precast concrete floors which will be covered by carpet.

Coverage: 1m² @ 11.5mm thick

Available in 20kg bags

Mastertop® P-10

An economical self-levelling floor underlayment. Suitable for use under carpet, ceramic tiles and non-critical vinyl applications.

Coverage: 4m² @ 3mm thick.

Available in 20kg bags.

Mastertop® P-15

Premium quality self-levelling floor underlayment. Suitable for use under vinyl, parquet, carpet and ceramic or natural stone tiles. It can be feather-edged or applied to a maximum thickness of 15mm. Floor coverings can be applied after 16-18 hours @ 20°C.

Coverage: 4m² @ 3mm thick.

Available in 20kg bags.

Mastertop® P-30

An economical self-smoothing floor underlayment. Ideal for use on floor areas that require bulk filling prior to the application of Mastertop® P-15. It may also be used to create falls to floor wastes or drains. Ready for floor leveller in 3 hours.

Coverage: 1m² @ 10mm thick.

Available in 20kg bags.

Mastertop® P-45

Rapid-setting, non-sagging material for creating ramps, coving, filling holes or penetrations prior to the application of Mastertop® P-10 or Mastertop® P-15. Ready for foot traffic in 45 minutes.

Coverage: 1m² @ 12.5mm thick.

Available in 20kg bags.

Mastertop® 540

An economical self-levelling, cementitious, non-structural floor overlay intended for use of poured insitu concrete floors. Mastertop® 540 has been specifically formulated to achieve a fast-setting, level surface suitable for foot traffic, rubber-wheeled equipment and occasional car usage.

Available in 20kg bags.

Mastertop® P Primer

General purpose acrylic primer for bonding of floor levellers to porous substrates. It also acts as a pore sealer to prevent air bubbles from rising through the applied leveller. Mastertop® P Primer can be diluted up to 1:3 by volume with water.

Available in 5 litre or 20 litre containers.

Mastertop® 1116

Water-based epoxy primer/moisture barrier. Used as a primer when applying a levelling compound over non-porous substrates such as tiles or terrazzo. Used as a moisture barrier over new or damp concrete.

Coverage: 4m² per litre.

Available in 4 litre and 20 litre kits.

PCI Gisogrund® 404

Primer suitable for both absorbent and non-absorbent substrates. For priming prior to the application of Mastertop® levelling compounds over ceramic tiles or terrazzo.

Coverage: 25-50m² (depending on absorbency of the substrate)

Available in 5 litre & 20 litre containers



The Chemical Company

BASF Construction Chemicals Australia Pty Ltd

Sydney Head Office & Export

Ph: (02) 8811 4200

Fax: (02) 8811 3299

Melbourne

Ph: (03) 9549 0300

Fax: (03) 9549 0399

Canberra (agent)

Ph: (02) 6280 6010

Fax: (02) 6280 7220

Newcastle

Ph: (02) 4961 3819

Fax: (02) 4940 8762

Adelaide

Ph: (08) 8139 7500

Fax: (08) 8139 7599

Perth

Ph: (08) 9366 2600

Fax: (08) 9366 2699

Brisbane

Ph: (07) 3633 9900

Fax: (07) 3633 9999

Darwin (agent)

Ph: (08) 8984 3269

Fax: (08) 8947 0504

Townsville

Ph: (07) 4774 7344

Fax: (07) 4774 7355

Kalgoorlie

Ph: (0417) 772 355

Mackay

Ph: (0418) 991 567

www.basf-cc.com.au

BASF New Zealand Ltd

Auckland

Ph: (09) 414 7233

Fax: (09) 414 7244

www.basf-cc.co.nz