

Application

Targeted for professional use as direct to inside of space diffusion method.

Technical Characteristics

Reference: Air Q 550, Model AQ550

Type: 1 Head Nebuliser

Particle Diameter: Typically less than 1 micron

Power Input

Input: 100-240 VAC at 0.6 A

Frequency: 50/60 Hz

Protection: Switching power supply

Internal Power: 12 VDC at 1.5 A
Backup Battery: Lithium 3V, #CR2032

Performance

Up to 850 cu. metres served With 1 air change per hour, cartridge will last 8 weeks Mulit-programmable start/stop times (up to 3 per day) 50 adjustable output settings Top or front output location

Wall Mounting Mechanism

Nylon mounting plate and screws included Ceiling track mounting optional

Cartridges

1 x 250 ml or 265 ml cartridge containing fragrance and odour treatment products

Dimensions

Height x Width x Depth: 219mm x 222 mm x 98mm

Total Weight: 2.2 kg

Enclosure & Environment

Nylon plastic enclosure with lockable door 0 to 40 degrees Celsius operating temperature 85% or less operating relative humidity



the odour management experts

Odour Control Systems (Aust) Pty Ltd P O Box 179 Islington NSW 2296 P: (02) 4907 8200 F: (02) 4969 4218

