

Australia

Platform Lift Company Pty Ltd 785 Pittwater Road, Dee Why, NSW 2099 Australia

Telephone: 1300 884 960 Fax: + 61 (2) 8580 5048

Email: info@platformliftcompany.com Web: www.platformliftcompany.com

United Kingdom

Platform Lift Company
Apsley Barns, Apsley, Andover, Hampshire, SP11 6NA
United Kingdom

Telephone: +44 (0) 1256 896000 Fax: +44 (0) 1256 896900 Email: info@platformliftco.co.uk Web: www.platformliftco.co.uk

United Arab Emirates

Platform Lift Company Middle East LLC
Office No. 408, 4th Floor Montana Building,
Za-Abeel Rd, Al-Karama, Dubai, UAE.
PO Box 111833, Dubai, United Arab Emirates

Telephone: +971 4 335 6118 Fax: +971 4 335 6119

Email: info@platformliftcompany.com Web: www.platformliftcompany.com designed, engineered and fitted... without compromise







dynamic

by working hand in hand with our customers, from project conception to completion, we have developed an impressive record of continuous global growth.



main provider in innovation and design

our clients include McDonalds Restaurants, Hugo Boss, Hilton Hotels, Monsoon, Laura Ashley, Mercedes Benz, Marks & Spencer, London Underground, Reserve Bank of Australia, Bondi Bathers Trust, Sydney Opera House, Austal Ships, Integral Energy, FACIA, DOTMAR, Qatar National Bank, Dubai Marina Hotel, Dubai Metro, Yas Island development and many more.



comprehensive range of services and maintenance packages

our fully qualified service and maintenance engineers maintain and support our products throughout their lifecycle.





A-Type platform lift

from manufacture to installation our A-Type lift is totally flexible

a favourite among architects and engineers with its high quality and flexible construction, the A-Type platform lift fits well into all types of environment. This platform lift includes a free-standing enclosure in your chosen RAL colour. Alternatively, a glazed or stainless steel finish is available. The A-Type has a maximum travel of 12 metres and 5 stops.

operation

with its elegant controls and call-stations incorporated within the lift shaft, it is designed to give less able persons, including the visually impaired, ease of use.

no pit required

this lift can be installed direct to the floor, which means no expensive costs for excavation.

no machine room

as the control system is incorporated within the shaft, there is no need for a separate machine room.

safety first

all extreme edges of the platform have movable safety edges which immediately stop the lift when touched. The speed is limited and the control system is hold-to-run type. It is equipped with an emergency stop and alarm device.

technical data

Rated load

- 400kg / 1000kg

Rated speed

- 0.15m/s

Lifting height

- 12m - 5

Number of stops

- Hold-to-run

Control system

Drive system

- Double V belt transmission to a rotating nut assembly. Driving nut and safety nut working on a fixed hanging

Power requirements - 415v or 240v









B-Type platform lift

stylish and reliable solution

a simple screw and nut driven lifting platform for mainly external applications. The B-Type can also be installed internally, travelling a maximum of 2m. With its open design covered by toughened and laminated glazed panels, it provides a stylish and reliable platform lift solution.

no pit required

the B-type platform lift doesn't require a pit as the platform lift comes with an internal ramp.

operation

"Saloon" type doors allow easy access to the platform. Control buttons are easy to handle for the operator with "hold-to-run" operation.

safety first

safety is of the utmost importance for the open type platform lift. A safety plate covers the whole underside of the platform, if the plate is touched the lift stops immediately.







technical data

Rated load

- 300kg

Rated speed Lifting height - 0.1m/s

Number of stops

- 2m - 2

Control system

- Hold-to-run

Drive system

- Double V belt transmission to a rotating nut assembly. Driving nut and safety nut

working on a fixed hanging screw.

Power requirements - 415v or 240v

"provided a great service throughout the initial stages, installation and after service"

Richard Paintin The Outdoor Group







a shining example of elegant style and performance

our E-Type range is formed of two stylish platform lifts capable of travelling a maximum of 1m. This low rise lift blends in and can be easily installed into any environment.

design

this low rise lift's look and adaptability make it a winner with architects.

rapid installation

with almost no exception, the E-Type range can be installed, tested, commissioned and handed over within a single day.

safety first

all extreme edges of the E-Type low rise platform lift have movable safety edges which immediately stop the lift when touched. Bellows prevent access to the underside of the lift when in the up position. "installed within such tight spaces, maximising shop space... great products"

Accessorize -Monsoon Stores









Rated load - 250kg
Rated speed - 0.1m/s
Lifting height - 1m
Number of stops - 2

Control system - Hold-to-run

Drive system - Screw and nut/hydraulic

Power requirements - 240v





Stairlift

straight and curved stairs, fitted effortlessly

our stylish stairlift models are fully automatic with electronically controlled platforms and barrier arms. The platform and arms neatly fold away on a smooth operating rail when not in use, leaving the maximum width of the stairway for pedestrians, creating the ideal low-rise solution.

rapid installation

the platform stairlift can be either floor or wall mounted and installed within two days by our fully qualifi ed installation engineers. The only requirement is a dedicated single-phase power supply.

safety first

all extreme edges of the platform have movable safety edges which immediately stop the lift when touched.

technical data

Rated load - 230kg
Rated speed - 0.1m/s
Control system - Hold-to-run
Drive system - Rack and pinion
Power requirements - 240v single phase





