CHECK IT OUT

Compare the AM-BOSS pull-down access ladder with other makes. Do they have all these important features?

- Complies to the Building Code of Australia
- CodeMark Certified
- Welded Aluminium Stair
- Concealed Hinges
- Draft Seal All Round
- Neat Ceiling Panel No Visible Screws
- Slim Metal Architrave
- Made to suit exact ceiling height
- Stair Fitted off Panel

V

V

- for better Hand and Foot Hold
- Our Frame Height matches Ceiling Joists
- Trouble-Free Spring Balancing
- Commercial Strength
- 12 Months Guarantee (Commercial and Industrial)
- All commercial series pull-down access ladders come with a Standard Handrail
- Fully Assembled
- Fitted Fixing Clips for Easy Installation
- Wholly Australian Made
- 150kg Load Capacity (At Any Given Point) Tested by Metlabs

That is why AM-BOSS products are the best and most advanced.

WHICH MODEL?

COMMERCIAL SERIES

MODEL	Access-Boss™	BIG-BOSS™
	Cutout: 1220mm x 570mm	Cutout: 1220mm x 770mm
	Tread Width: 400mm	Tread Width:500mm
	On-grade at 68° approx.	On-grade at 68° approx.
2153	CEILING HEIGHT	CEILING HEIGHT
	2150-2300mm	2150-2300mm
	Exact Ceiling Height Required	Exact Ceiling Height Required
2345	CEILING HEIGHT	CEILING HEIGHT
	2300-2450mm	2300-2450mm
	Exact Ceiling Height Required	Exact Ceiling Height Required
2460	CEILING HEIGHT	CEILING HEIGHT
	2450-2600mm	2450-2600mm
	Exact Ceiling Height Required	Exact Ceiling Height Required
2680	CEILING HEIGHT	CEILING HEIGHT
	2600-2800mm	2600-2800mm
	Exact Ceiling Height Required	Exact Ceiling Height Required
2830	2800-3000mm	2800-3000mm
	Exact Ceiling Height Required	Exact Ceiling Height Required
	Exact Centing Height Required	Exact Cetting Height Kequirea
	Access-Boss™	BIG-BOSS [™]
MODEL	Cutout: 1520mm x 570mm	Cutout: 1520mm x 770mm
MODEL	Cutout: 1520mm x 570mm Tread Width: 400mm	Cutout: 1520mm x 770mm Tread Width:500mm
MODEL	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx.	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx.
	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT
MODEL 3020	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm
	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required
3020	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT
	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm
3020	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT
3020	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm
3020	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm
3020 3240	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT
3020 3240	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm
3020 3240 3460	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required
3020 3240	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm
3020 3240 3460	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm Exact Ceiling Height Required	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm Exact Ceiling Height Required
3020 3240 3460 3680	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm Exact Ceiling Height Required CEILING HEIGHT	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm Exact Ceiling Height Required CEILING HEIGHT
3020 3240 3460	Cutout: 1520mm x 570mm Tread Width: 400mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm Exact Ceiling Height Required	Cutout: 1520mm x 770mm Tread Width:500mm On-grade at 68° approx. CEILING HEIGHT 3000-3200mm Exact Ceiling Height Required CEILING HEIGHT 3200-3400mm Exact Ceiling Height Required CEILING HEIGHT 3400-3595mm Exact Ceiling Height Required CEILING HEIGHT 3600-3800mm Exact Ceiling Height Required

Available from:

AM-BOSS Access Ladders Pty Ltd 11-13 Maida Avenue SUNSHINE NORTH VIC 3020 Tel: (03) 9310 8788 Fax: (03) 9367 9673 Email: <u>amboss1@bigpond.com</u> Web: www.ambossaccessladder.com.au



COMMERCIAL & INDUSTRIAL

www.ambossaccessladder.com.au





CM20058






SUSPENDED CEILINGS:

AM-BOSS pioneered installations of access ladders into suspended ceilings, and has done so for over twenty years. **AM-BOSS** developed a design using galvanized steel profiles, specially made to suit the suspended ceiling type of application. Galvanized hangers and bracing will keep the galvanized steel support frame rigid 40mm above the suspended ceiling. The **AM-BOSS** 'Access-Boss™' or 'Big-Boss™' pull-down access ladder is then installed into the support frame; the zinc sealed steel architrave of the access ladder is strong enough and will support the ceiling around it. A fixed ceiling space ladder will continue from the top of the pull-down access ladder to the roof hatch or plant platform.

In grid ceilings **AM-BOSS** always installs the '**Access-Boss**TM' access ladder into one grid panel.



Manufactured in Australia since 1979 by AM-BOSS Access Ladders Pty Ltd

BUILDING CODE OF AUSTRALIA (BCA): CodeMark Certified

AM-BOSS Access Ladders Pty Ltd were the first to manufacture pull-down access ladders that complied with the Building Code of Australia (BCA), over a decade ago. Conformity was validated through the CSIRO Appraisal Scheme until December 2009, when the CSIRO ceased its Appraisal scheme.

The National Construction Code (NCC) was developed to incorporate all on-site construction requirements into a single code. The NCC comprises the BCA (Volumes One and Two), and the Plumbing Code of Australia as Volume Three, into its series and is the National Technical Document which sets the standards of building work in Australia, including non-residential buildings.

The compliance of building products and systems with the BCA is provided through the CodeMark Scheme. Products accredited through this scheme are automatically recognised nationally and internationally as being compliant with the Code in Australia and New Zealand. **Relevant legislation requires building control authorities to accept CodeMark Certified products.**



COMMERCIAL / INDUSTRIAL ENVIRONMENTS:

AM-BOSS access ladders are a quality product and are widely accepted in residential, commercial, industrial and government buildings. **AM-BOSS 'Access-Boss™'** and **'Big-Boss™'**, **commercial series** are constructed in welded aluminium, are strong and durable and all steel parts, including springs, are zinc plated. **AM-BOSS** also manufactures the **'AM-BOSS Inferno-Boss™'** pull-down access ladder, Fire-rated to AS1530.4-2005 with a 90/90 rating; and the **AM-BOSS Heavy Duty** commercial series which are rated at **400kg**.

The access ladder is mounted in such a way as to allow clearance between the steps, and the ceiling hatch, for safer footing. Our counter-balance system is designed so that when the hatch is closed, the springs are almost relaxed – ensuring lifelong service! The fully assembled hatch enables the **'Access-BossTM'** or **'Big-BossTM'** to blend into your ceiling with practically little intrusion.

All variations in ceiling heights can be accommodated by various model types and options.



OTHER HANDY INFORMATION:

OH&S now plays an important role in ensuring a safe work environment. **AM-BOSS access ladders** deliver safe access to walk-ways, plant platforms and inside of roof cavities. Access to roof tops incorporating an **AM-BOSS access ladder** and ceiling space ladder to the underside of the roof access hatch, with or without telescopic stanchions, makes servicing air conditioning plants on the roof a safe and easy operation.

AM-BOSS Access Ladders Pty Ltd caters for individual work environments and 'one-off' specials. Our scope of works include (but are not limited to) fixed aluminium access ladders, steel vertical access ladders, parapet access ladders, caged access ladders, pull-out / push-in access ladders, suspended platforms, guard-railing, walkways, platforms; anchor points, fall-arrest systems; etc.

AM-BOSS also manufacture swing down ladders suited for indoor and outdoor use, and many other types of ladders.

