



Recommended Installation Height

From Floor to Top of Hand Dryer =
950mm

From Floor to Bottom of Hand Dryer =
290mm

Complies with Disabled Persons
Requirements

Electrical Installation Options

Simple electrical connection by plug and
lead as supplied, or can be direct wired by
electrician.

*Visit website for detailed installation
instructions*

EXECUTIVE JET DRYER JDEXEC2-X [X = S (Silver), W (White)]

TECHNICAL SPECIFICATIONS

Electrical

Input voltage: 230-240V AC, Single Phase 50Hz

Rated Power: 1200W, 5 Amp

Motor Type: Vacuum, Brush Resistance Motor (Heat from motor is used to warm air)

Energy Consumption per use: 0.004 kWh

Standby Power: 1 W

Construction

H- 660 x W- 330 x D - 230mm

Polycarbonate – ABS casing with antimicrobial additive to all external surfaces, Burn Proof

Colour Finishes: Silver, White, Custom (Upon Request)

Water Protection: IP33

Filtration

Anti-bacterial coated Pre Filter,

HEPA Filter (H13 - 99.95% @ 0.3)

Aromatic Fragrance Stick

Operation

Infra-Red Touch Free Operation

Hand Drying Time: Approx. 10 - 12 Seconds

Airflow: 540+ kph in High

Operating Noise: Approx. 65 DbA in Low, 70 DbA in High

Water Holding Tank: 500ml

Air Filter and Water Tank Sensors

Weight

Unit Weight: 9kg

Packaged Weight: 12kg

Warranty

3 year Parts, 1 year Labour (Limited to 500,000 Uses)

Product Certification

Approved to IEC/EN60335-1 and IEC/EN60335-2-23

Compliant to EMC directive according to EN55014-1, EN55014-2, EN61000-3-2, EN61000-3-3 (CTICK N27284)