

|   |   |
|---|---|
| <b>Product</b>  | Equideck® Insulated Roof Panel  |
| <b>Product Description</b>                                      | Equideck® EPS-FR insulated roofing panel system provides a flat and standing-seam like roof profile made from Colorbond® steel, a prepainted ceiling underside and high performance insulated core in an all-in-one roofing panel. Equideck® is made using Australian-made Colorbond® steel for durability and delivers a long-spanning and thermally efficient roof.   |
| <b>Supplier</b>   | BONDOR®   |
| <b>Contact Number</b>   | 1300 300 099  |
| <b>Website</b>  | www.bondor.com.au   |
| <b>Product Overview</b>   |   |
| <b>Core</b>   | EPS-FR<br>(Expanded Polystyrene with fire retardant)  |
| <b>Width (cover mm)</b>   | 1200  |
| <b>Thickness (mm)</b>   | 50, 75, 100, 125, 150, 200, 250<br>(non-std options available)  |
| <b>Length</b>   | Up to 16m (check for availability)  |
| <b>External Material</b>  | Bluescope® Colorbond® Steel 0.6mm   |
| <b>External Finishes</b>  | Plain, Ribbed, Satinline  |
| <b>External Colour Options</b>                                  | Surfmist®   |
| <b>Internal Material</b>  | Bluescope® Colorbond® Steel 0.6mm   |
| <b>Internal Finishes</b>  | Plain   |
| <b>Interior Colour Options</b>                                  | Surfmist®   |
| <b>Pitch</b>  | 3 degree minimum  |
| <b>Paint System</b>   | AS/NZS 2728 & AS 1397   |
| <b>Accreditations</b>   | Codemark Certificate Number CM40195   |
| <b>Acoustic Properties</b>                                      | Rw 24 - 25 depending on thickness   |
| <b>Material Group Numbers</b>                                   | C1 .10 Group 1 & 2  |
| <b>Bushfire Attack Level</b>                                    | BAL-40 (All exposed core to be covered with flashing)   |
| <b>Technical Properties</b>                                     |   |
| <b>Thermal - AS/NZS 4859.1</b>                                  |   |
| <b>Total R-Value (m²K/W)</b>                                    | 50, 75, 100, 125, 150, 200, 250mm Equideck® delivers Total-R value of 1.4, 2.1, 2.7, 3.3, 3.9, 5.2, 6.5 for insulation average temperature of 15°C. Contact us for other temperatures and different EPS-FR core grades.   |
| <b>Acoustics - AS 1191, AS/NZS 1276 &amp; AS/NZS ISO 717 .1</b> |   |
| <b>Rw Value (dB)</b>  | Equideck® has been tested in accordance with the requirements of AS 1191. The Weighted Sound Reduction Index (Rw) of the panel is calculated using AS/NZS 1276 and AS/NZS ISO 717.1 respectively with acoustic values of Rw 24 - 25 depending on thickness. Refer to Bondor® Australia for your specific application.   |
| <b>Fire</b>   |   |
| <b>Fire hazard properties</b>                                   | AS/NZS 1530.3   |
| <b>Ignitability Index</b>                                       | 0   |
| <b>Spread of Flame Index</b>                                    | 0   |
| <b>Head Evolved Index</b>                                       | 0   |
| <b>Smoke Index</b>  | 2-3   |
| <b>SMOGR<sub>RC</sub></b>                                       | < 100   |
| <b>Material Group Numbers AS 5637.1 / AS ISO 9705</b>           | Equideck® EPS-FR steel skinned insulated building panels conform to the requirements of the BCA Specification C1 .10a as either Group 2 or Group 1 depending on the thickness and construction detail.<br>Group 1 - Panel up to 250mm thick with steel 'wall-wall' and 'wall-ceiling' angles fixed with steel rivets or screws at maximum 300mm centres is classified as Group 1 .<br>Group 2 - Panel up to 150mm thick with aluminium 'wall-wall' and 'wall-ceiling' angles fixed with aluminium rivets or screws at 300mm centres is classified as Group 2. Panel thicker than 150mm requires steel 'wall-wall' and 'wall-ceiling' angles fixed with steel rivets or screws at 300mm centres to be classified as Group 2. |
| <b>Bushfire Attack Level AS 3959</b>                            | Equideck® is suitable for use as roof covering for Class 1 and 10 buildings to be constructed in designated bushfire prone areas that have a BAL-40 or less.  |

## Structural - AS/NZS 1170, AS 1562.1, AS4040

|   |  |
|---|--|
| <b>Span Table</b>                       | Bondor® provides the latest Ultimate Limit State Span Tables developed specifically for Australasian conditions, in accordance with AS/NZS 1170, AS 1562.1 & AS 4040. Refer to Span Tables for detailed design guidelines and Span Tables for both Non-Cyclonic Regions A & B. Extended Span Tables for Residential Applications are also available. Refer to Span Table Notes for design guidelines relating to fixing, and deflection limits. The panel design shall be specified by the certifying engineer as determined from the Span Tables.   |
| <b>Support Details</b>                  | The support spacing shall be specified by the structural engineer as determined from the Span Tables.  |
| <b>Safe Handling &amp; Installation</b> |  |
| <b>Panel Length</b>                     | Up to 16m, however site, transport and wind load restrictions can limit panel length.  |
| <b>Storage</b>                          | Panels should always be kept dry and if placed on site, stored off the ground, slightly inclined, allowing adequate drainage and ventilation of the panel pack. No other materials to be stored I stacked on top of panel pack.  |
| <b>Handling</b>                         | In the event of manual handling, careful consideration should be given to panel weight and appropriate PPE. Consider using mechanical aides if necessary.  |
| <b>Safety</b>                           | The contractor is to determine and use safe working methods throughout the installation and construction period, which complies with OHS requirements. A safe work method template (although NOT project specific) is available from Bondor®.  |
| <b>Supporting Frame</b>                 | The builder is to ensure that the substrates including slabs and kerbs; and sub frames are straight, true and fit for purpose.   |
| <b>Fixing</b>                           | Fixings are to meet the requirements of Bluescope TB-16 Fasteners for Roofing and Walling Product Selection Guide. Fasteners must be manufactured from high grade carbon steel with a minimum class 4 anti-corrosion coating as per Australian Standards. Refer to Bondor® Roofing Construction Details & Span Tables Notes for design guide relating to screw fixing and IPCA for cold storage compliance.  |
| <b>Flashing</b>                         | Flashings are manufactured from 0.55mm Bluescope Colorbond® steel and installed to AS 1562.1 or as otherwise specified in the Bondor® Cold Storage or Standard Construction Drawings. Aluminium can be used if there is no Group Number requirement. Refer to IPCA for cold storage compliance.  |
| <b>Sealant</b>                          | Sealant to be neutral cure and meet recommendations for sealants as per Bluescope TB-9 Sealants for Exterior Finishes. Silicon, polyurethane, butyl mastic and acrylic based sealants may be appropriate if neutral cure and recommended by their manufacturer for use on Colorbond® steel and for the application. Sealant to be placed between flashings/angles and panel and between panel joints as shown on the Bondor® Standard Construction Details.  |
| <b>Installation</b>                     | <p>Installation as per the Bondor® Standard Construction Details.</p> <ul style="list-style-type: none"> <li>• Panels are to be cut &amp; trimmed to ensure a flush finish.</li> <li>• Panels are to be confirmed square &amp; plumb as per project requirements.</li> <li>• Panels are to be cut with a suitable metal cutting circular type saw. Angle grinder is not recommended.</li> <li>• Appropriate lifting equipment to be used for roof panels.</li> <li>• Roof panels to be installed and fit as close and tight as possible.</li> <li>• Ensure appropriate gutter cutbacks for drainage.</li> <li>• Roof sheets endlap must be designed and installed with correct roof pitch, water run-off and use approved Securelap End Lap roof system.</li> <li>• Fasteners are to be installed without overtightening to prevent distortion of panel surfaces. Ensure weathertight contact of washer seal with panel surface.</li> <li>• All accessories must be compatible material properties with Bluescope Colorbond® Steel.</li> <li>• Penetrations for outlets, vents, flues etc. are to be flashed &amp; sealed with appropriate materials. Refer Flashing Details above.</li> <li>• Gaps to be filled with a suitable sealant or foam filler.</li> <li>• Refer to AS1562 &amp; SA HB 39 for roofing/cladding installation &amp; plumbing.</li> <li>• Refer to Bondor® Standard Construction Details &amp; Fixing Details above for fastener requirements.</li> <li>• Remove all swart and any foreign matter immediately from all panel surfaces as per Bluescope TB-5 Swart staining of steel profiles.</li> </ul> |
| <b>Maintenance</b>                      | Refer to Bluescope TB-4 Maintenance of Colorbond® and Zinalume® Steel and the relevant Bondor® maintenance information.  |
| <b>Warranties &amp; Disclaimers</b>     |  |
| <b>Warranty</b>                         | Bondor offer a conditional warranty for Equideck® for use as architectural roofing panels and cool rooms of up to 10 years from install date for projects on an application basis, dependent on project location, design, installation, end use, environmental conditions and maintenance of the product. Please contact the Bondor sales team with your specific project details for more information on the available conditional warranties.  |
| <b>Disclaimers</b>                      | Under certain light conditions this product may show an undulating surface which can vary depending on exterior profile and steel gauge selection as well as the environments varying light conditions.  |