


ELABANA



To view colour swatches for each state refer to www.monier.com.au

An ideal tile for enhancing both modern and Mediterranean designs, the prominent roll of Elabana's profile adds eye-catching style to your roof.



TILES USAGE WITH WASTAGE [+/-2%]Approx. 11.0 tiles per sqm.

TILE COVERAGE (±2%) Approx. 9.90 tiles per sqm.

DIMENSIONS (±2%)Length420mm (415mm in NSW)Width329mm

 MASS (±2%)

 Per tile
 4.50kg

 Per m²
 44.0kg

HEAD LAP ADJUSTMENT (MM) 80 – 110

FEATURE High roll

COLOUR APPLICATION Colour On

RECOMMENDED BONDING Straight bond

ROOF PITCH Minimum Pitch with Sarking: 15°

Minimum Pitch without Sarking: 20°

Please consult the Design Guide at Monier.com.au for installation requirements applicable to your project.

Please refer to AS2049 for acceptable tolerance to these measurements stated above.



CONCRE^T ACCESSORII F MON **CONCRETE** LENGTH (MM) ACCESSORY WIDTH (MM) HEIGHT (MM) ANGLE (DEGREE) WEIGHT (KG) Parbarge 420 420 248 126 84 4.9 248 == : == : == Starter 80 420 420 250 80 120 2.8 250 120° 3-Way Apex (butt & overlapping) 391.7 413.3 135 135 3.8 Ridge 420 80 120 420 250 80 3.4 120° 250 Ridge Saddle _205 175 205 250 175 120 3.3 120° 250 ашв Gable Finial — Scroll 280 245 245 240 280 120 5.1 120° 240 Apex Finial — Scroll 385 320 385 420 320 120 6 120 120' Spoon-Starter 410 125 410 395 125 120 6 395 120°