



Channel

PRODUCT FACT SHEET

Sustainable Style

COMMERCIAL | RESIDENTIAL | CUSTOM

cedarsales.com.au

Create strongly-defined shadow lines

Channel provides an immaculate design feature for discerning tastes. This minimalistic profile is ideal for cladding the exterior of architecturally-designed buildings. Square, flat faces and deep, narrow channels produce an effect that's simply stunning. Create dynamic shadow lines in perfect alignment with ease.

FEATURES + BENEFITS

- Deep narrow channels producing sharp defined shadow lines.
- Smooth, flat faces without bevel for a flat, square and straight finish.
- Machined drip grooves to suit vertical installation.
- Can be painted, stained or left unfinished to grey naturally.
- Provides improved insulation and reduced noise penetration.
- Improved Green Star rating with FSC®, PEFC™ and GreenTag^{Cert™} GreenRate Level A Certification.

IDEAL USES

- Feature walls
- Commercial projects
- Residential projects
- Facades
- Public spaces



COMBINATION OF CLSS5C 71 X 26, CLCG19C 115 X 26 [LEFT TO GO GREY WITH AGE AS PER ARCHITECT'S DESIGN]



CLS5E 120 X 18



CLSS5C 120 X 26 [PAINTED GREY BY CLIENT]

PROFILES AVAILABLE

CHANNEL [FEATURES 5MM CHANNEL WIDTH WHEN JOINED]



CLS5S 86 X 12



CLS5S 133 X 12



CLS5E 70 X 18



CLS5E 120 X 18



CLS5E 120 X 18 KBS
[KNOTTY GRADE / SAWN FACE]



CLS5E 170 X 18



CLSS5C 71 X 26



CLSS5C 120 X 26



CLSS5C 170 X 26



CLSS5C 220 X 26

CHANNEL WITH CENTRE GROOVE [FEATURES 19MM CHANNEL WIDTH WHEN JOINED]



CLCG19C 115 X 26



CLCG19B 115 X 38

INSTALLATION

For secret nail fixing and in-depth installation instructions, visit cedarsales.com.au



CHANNEL SIZES + SPECS

PROFILE CODE	COVER (MM)	THICKNESS (MM)	MAX SPANS (MM)	ORDER OPTIONS	
CHANNEL					
CLS5S 86 X 12	86	12	600		<input type="checkbox"/>
CLS5S 133 X 12	133	12	600		<input type="checkbox"/>
CLS5E 70 X 18	70	18	600		<input type="checkbox"/>
CLS5E 120 X 18	120	18	600		<input type="checkbox"/>
CLS5E 120 X 18 KBS (KNOTTY)	120	18	600		<input type="checkbox"/>
CLS5E 170 X 18	170	18	600		<input type="checkbox"/>
CLSS5C 71 X 26	71	26	600		<input type="checkbox"/>
CLSS5C 120 X 26	120	26	600		<input type="checkbox"/>
CLSS5C 170 X 26	170	26	600		<input type="checkbox"/>
CLSS5C 220 X 26	220	26	600		<input type="checkbox"/>
CHANNEL WITH CENTRE GROOVE					
CLCG19C 115 X 26	115	26	600		<input type="checkbox"/>
CLCG19B 115 X 38	115	38	600		<input type="checkbox"/>

Suitable for external cladding

Custom orders available – contact Cedar Sales rep

Cutek® pre-oiling available [clear penetrating external oil]



Fire protection



Acoustic properties



Unrivalled sustainability



Thermal protection



Structure & performance

Choose Cedar Sales and specify with confidence

Cedar Sales is committed to quality and performance you can count on. Our genuine architectural timber innovations are proven to perform where it matters most. As part of our commitment to provide market-leading quality and integrity, Cedar Sales welcomes third-party testing and certification across fire, acoustics, structural performance and sustainability.



HEAD OFFICE

Manufacturing Plant | National Distribution Warehouse

150 Toongarra Road
Wulkuraka QLD 4305
PO Box 5043, Brassall QLD 4305

P 1800 156 455
F +61 (07) 3281 4322
E info@cedarsales.com.au

MELBOURNE OFFICE

Showroom | Warehouse

82 Wedgewood Road
Hallam VIC 3803
P +61 (03) 9708 6572

cedarsales.com.au

Sustainable Style

COMMERCIAL | RESIDENTIAL | CUSTOM

Photographs, images and drawings used herein are for illustration purposes only. Colours, grades and finishes on actual products may vary. All timber products will vary from samples. Being a natural product, expect sheen, tonal and colour variation and natural features including knots, grains and grain impressions. We recommend viewing all products prior to installation. Cedar Sales' is unable to offer any specific performance warranties for its products because of the wide variation in applications possible. These variables include but are not limited to; situation, design and structure, aspect and differing exposure to the weather. For more details, visit cedarsales.com.au/terms-and-condition-of-trade.