



solid solutions to better hardscapes

Adhesive

STRONGEST

Adhesive on the Market for Professional Applications

TIME-TESTED

Proven Performance for Over 25 Years

Rapid-Set Polyurethane

NEW!

**FASTEST
SET-UP TIME
on the Market!**



Benefits

- ▶ Fastest set-up time on the market!
- ▶ High temperature adhesive suitable for firepits
- ▶ For use on dry or damp surfaces
- ▶ Premium, long lasting strength
- ▶ Interior/exterior use
- ▶ Specially formulated for use on construction and landscape projects



SRW Products: Providing All-Round Protection

NEW 2015
PRODUCT



Rapid-Set Polyurethane

We're proud to introduce our newest addition to the SRW Adhesive family. It is specially formulated for construction and landscape projects that require a fast set-up time. This adhesive has proven to be a premier choice, providing a fast, but permanent bond. It can be used on almost any material, even non-porous substrates such as foam, metals, etc.

User Tips

1. When using on tumbled products, we recommend using a 10mm bead. Make sure surface is clean of any dust, dirt or material that may deter proper adhesion.
2. For steps or high-traffic areas, wait 48 hours before use and 4-5 days for cure.
3. If surface has grooves, make sure adhesive is bonding to both surfaces.
4. Not intended for continuous submersion or use below the waterline.
5. Not for use on plastic, rubber, or fiberglass materials.
6. When using on applications that need optimal water flow, consider the adhesive application patterns to the bottom right.



APPLICATIONS:

- ▶ Retaining walls
- ▶ Pavers & Brick
- ▶ Concrete
- ▶ Natural stone
- ▶ Pool copings
- ▶ Firepits
- ▶ Metal
- ▶ Wood
- ▶ Foam
- ▶ Vinyl & PVC

Works on most common landscaping and construction materials.

Application temps:

Above 4°C for adhesive, 0°C for surfaces

Method of application: Caulking gun.

Lightly mist surface for faster set-up.

Shelf life: 12 months

Working time: 15 minutes

Storage: Store in a cool, dry place in upright position out of direct sunlight. Will not freeze or be damaged by low temperatures.

Coverage

Approximate length of bead according to container size & bead diameter

Bead Size	10 oz	28 oz
6.0 mm bead	9.7m	27.1m
9.5 mm bead	4.2m	10.6m

Rapid-Set Polyurethane

Moisture-based cure for a fast and strong permanent bond

Application surface temps above 0°C

1 year shelf life

Directions

1. CLEAN SURFACE

- ▶ Remove oil, grease, ice, water, or dirt that may interfere with bond.

2. PREPARE TUBE

- ▶ Cut tip at slant for 6mm or 9.5mm bead
- ▶ Puncture seal
- ▶ Place tube in gun

3. APPLY

- ▶ Apply only the amount you can cover in 10 min. See user tips for suggested patterns

4. SET IN PLACE

- ▶ Set block, reposition if needed
- ▶ Do not smear or use trowel

APPLICATION PATTERNS FOR OPTIMAL MOISTURE DRAINAGE

Concrete Overlay

Retaining Wall

