

DESIGN DEPARTMENT - PRODUCT SPECIFICATION SHEET

DESIGN NAME:	EchoPanel®Mura Quattro
SUPPLIER:	Woven Image
ORIGIN:	Australia/China
COLOURS:	7
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m²
PATTERN REPEAT:	Vertical: 75cm, Horizontal: 58cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	500m/colour 1,000m/design
PERFORMANCE COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	ISO 9705: Group 1 AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions
USE:	ASTM DE116 Dato: 4 0 02 mg/mg//bg (7 days)
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02mg/m²/hr (7 days)
ENVIRONMENTAL:	EchoPanel® Mura achieves GreenTag Certification LCARate: Bronze, GreenRate: Level B

ISSUE DATE: 21.3.16

