

Key benefits:

- Proven**
Sucessfully used by road authorities, councils and developers
- Effective noise control**
Minimum sound transmission loss of 37dB
- Design flexibility**
Easy to create impressive decorative designs, excellent for curves, corners and slopes
- Strong and durable**
Steel reinforced, resists high wind loads, vandals, fire and termites
- Easy to install**
Rapid installation with minimal site impact



Hebel Custom Routing

Hebel panels can now be custom routed to a design of your choice.

If you are looking for a unique look for your next project, consider the addition of architectural shadow lines, geometric patterns or even a full mural effect.

For more information, call CSR Hebel on 1300 369 448



HELI124 OCT16

For more information on Hebel SoundBarrier please call **1300 369 448** or visit www.hebel.com.au



SoundBarrier acoustic barrier systems



Making Light Work of Noise Abatement

Hebel® SoundBarrier™ is a highly effective acoustic barrier system that produces significant reductions in noise levels such as those emanating from roads, freeways and rail corridors.






SoundBarrier panels are steel reinforced Hebel Autoclaved Aerated concrete (AAC), a solid masonry product that is very strong yet 25% the weight of standard masonry and quick to install.

The standard SoundBarrier system consists of galvanised universal beams with concrete foundations. Hebel panels are placed horizontally between or against these columns and are held in place by galvanised steel angles. The versatility of post connections allows for restricted access installation for cantilever or radius noise walls.

SoundBarrier can be further enhanced by the addition of decorative post treatments, capping, routed patterns or attached featurework.

Technical Information



Hebel SoundBarrier Technical Detail		
R _w - thickness	100mm	35db
	125mm	37db
	150mm	40db
	200mm	40db
Fire Rating	125mm	-/240/240
Panel dimension	600mm in width and up to 6000mm in length	
Universal beam	180ub to 250ub depending on height of barrier	
Equal angle	150x150 to a height of 2m	
Weight (kg/m)	100mm	36kg/m
	150mm	54kg/m
Compressive Strength	4.0MPa	

Note: the FRL stated in the table above is limited to horizontally installed 125mm (min.) thick panels for wall heights up to 6000mm.