



Turbo 3-in-1™

3-IN-1 PAPER TOWEL DISPENSER WITH WASTE RECEPTACLE AND AUTOMATIC ELECTRIC HAND DRYER HAS GONE HIGH-SPEED

Other New ASI JD MacDonald Hand Dryers



Turbo-Dri™



Turbo-Slim™



TRI-Umph™

Introducing the Turbo 3-in-1 (10-64672-2) Paper Towel Dispenser with Waste Receptacle and Hand Dryer. This convenient 3-in-1 unit holds up to 500 standard multi-fold paper towels, has an automatic high speed hand dryer that dries hands in less than 15 seconds and comes with a 26 litre waste receptacle that is covered by a spring-loaded lid that prevents used paper towels blowing out. Provided in a sleek satin finish, the cabinet door is held closed with 2 tumbler locks keyed alike. Trims are available to suit semi-recessed and surface mounting requirements.



SPECIFICATIONS

Turbo 3-in-1 Paper Towel Dispenser with Waste Receptacle and Automatic Electric Hand Dryer shall hold and dispense 500 standard multi-fold or 400 standard C-fold paper towels and shall have a waste capacity of 26 L. Dispensing of multi-fold or C-fold paper towels shall not require an additional adapter. Cabinet, door, dispenser and waste receptacle (WR) shall be type 304 stainless steel alloy 18-8. All exposed surfaces shall have satin finish and shall be protected during shipment by PVC film easily removable after installation. Cabinet shall be 20 gauge with a 16 mm wide perimeter trim to lay flush against wall and shall have no exposed fastening devices or visible seams. Full-face door shall be 18 gauge, fabricated from one piece with no miters or seams on face and shall have 13 mm square returns to the wall. Door shall be attached to cabinet body with a full length 4.8 mm diameter (Ø4.8) stainless steel multi-staked piano hinge and shall be held closed with two (2) tumbler locks keyed alike to other ASI JD MacDonald washroom equipment. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. WR shall have piano-hinge mounted closed top with spring-hinge closed flap door and hemmed edges for safety. Structural assembly of all cabinet components shall be of welded construction. Hand Dryer shall operate automatically from IR sensor that shall activate dryer when hands are placed in sensor zone. Complete dryer specifications and warranty information is contained in the spec sheet for model no.10-0199-2-00 (TURBO-Slim™). Complete dryer Owner's Manual (OM) and Installation Guide (IG) shall be provided with unit.

WALL OPENING: 358 x 1381 x 184 mm (minimum)

MODEL	TYPE	VOLTS@ 50/60 Hz	AMPS	WATTS	DRYING TIME	COVER
10-64672-2	Fixed nozzles for hands	220 ~ 240	4.2	1000	Automatic, Less than 15 seconds	White

AIRSPEED	MOTOR	H/P	RPM x 1000	FAN TYPE	AIR FLOW	HEATING ELEMENT	OUTPUT AIR TEMPERATURE
164 km/h ~252 km/h	Brush Type Dual Ball Bearings with 95°C Auto Reset Breaker	0.67	16-29 KRPM (Adj.)	Multi Inlet Centrifugal	42-60 CFM (71-102 m ³ /h) Adjustable by owner	325 - 500 W Nichrome wire with auto reset circuit breaker and thermostat adjustable by owner	55°C & 25°C Ambient room temperature adjustable by owner



© 2015 ASI JD MacDonald

ASI JD MacDonald
Melbourne (Head Office)
48 Smith Road, Springvale, Victoria 3171.
Phone: 1800 023 441 Fax: (03) 9548 1141
E-mail: enquiry@asijdmacdonald.com.au
Web: www.asijdmacdonald.com.au

ASI99860315