# ALUCOBOND®

## naturAL



# ALUCOBOND®

naturAL

### ALUCOBOND® of natural beauty

ALUCOBOND® naturAL surfaces amplify the natural beauty and character of aluminium to enhance the design of your architectural project. The finely textured aluminium surface scatters light for a close-up visual effect, while retaining the look and lustre of smooth aluminium from afar. It is the ultimate cladding solution for achieving the sophisticated tone that your architectural vision demands. Now, your entrance, columns, and pylons can make a bold statement - without upsetting your budget!

ALUCOBOND® naturAL offers you the same unequalled material properties for which all ALUCOBOND® products are known: extraordinary flatness and rigidity, excellent formability, low weight and outstanding weather resistance.

ALUCOBOND® naturAL surfaces are easy to clean and care for, unlike other metal sheets (i.e. solid sheets with a brushed surface). Both attractive and ingenious, ALUCOBOND® naturAL is the ideal material for Interior and Exterior Architecture, and just another reason why ALUCOBOND® is "The World's Favourite Aluminium Composite Material".

Selecting ALUCOBOND® Material for projects which require environmental friendly materials is literally a natural choice. ALUCOBOND® is fully recyclable.





### **Specification**

Thickness	4 mm - (3 mm*)
Standard Width	1250 mm - (1500 mm*)
Special Width	Upon request
Length	2000 - 6800 mm
* 11	

\* Upon request

### Note

ALUCOBOND® naturAL is available as ALUCOBOND® and ALUCOBOND® plus (ALUCOBOND® A2 on request). Minimum order quantities apply.

For more information and available specification please refer to the manufacturer or your nearest ALUCOBOND® representative. To avoid possible reflection differences, panels must be installed in the same direction as marked on the protective peel-off foil. All aluminium alloys have minute variations that occur during the production process. Additionally, the rolling direction of the ALUCOBOND® naturAL surface structure affects how light is reflected. Such effects cause subtle differences in color and sheen and are common for all natural, non-coil coated metal surfaces. In order to minimize these variations in colour and appearance, all ALUCOBOND® naturAL aluminium composite panels for a project respectively an elevation of a project should originate from the same batch (see labels on the pallets). Furthermore, panels should be installed in the same direction as marked on the protective peel-off foil. However, 100% uniformity in colour and brightness of such a natural surface is not feasible.

We will be pleased to advise you on the special characteristics of **ALUCOBOND® naturAL** surfaces.

Please refer to the separate data sheets.



# ALUCOBOND®

## **International Contacts**

### Europe / Middle East / Africa /

3A Composites GmbH Alusingenplatz 1 D-78224 Singen, Germany Phone: +49 77 31 80 23 47 Fax: +49 77 31 80 28 45 info.eu@alucobond.com

### Asia / Pacific

Alucobond (Far East) Pte. Ltd. 25 International Business Park #03-56 German Centre Singapore 609916 Phone: +65 6562 8686 Fax: +65 6562 8688 info.ap@alucobond.com



#### 3A Composites – A true "global player"

- Sales offices and production plants in Europe, North and South America and Asia
- Wide range of available panels
- Partnerships with leading distributors
- Professional sales teams



3A Composites GmbH Alusingenplatz 1 D-78224 Singen, Germany info.eu@alucobond.com www.alucobond.com