At Nuplex we make sure that our flooring products tread lightly on the environment.



In response to a growing need in the building industry for the adoption of green building programs and technologies, Nuplex Construction Products offers a wide range of products which are in line with the Green Building Council of Australia's ideal to contain ultra low VOC (Volatile Organic Compounds) emitting materials. Listed below is part of a growing list of 'green' Nuplex Construction Products.

AQUACOLOUR

A water-borne, two-pack white epoxy coating for walls.

AQUAKEM

A water-based epoxy coating for waterproofing interior floors and walls. Used for curing seepage and dampness problems on interior surfaces of basements, tunnels, floors grade car parks, etc.

SURECOTE 500 SERIES

Trowel applied epoxy floor topping with low odour during applications. Used where chemical resistance to alkaline chemicals is required. Slip resistant and impervious make it ideal for food preparation.

SURECOTE 200, SURECOTE CLEAR UV

Roll-on, chemical resistant, protective coatings for internal surfaces. Used for sealing internal concrete floor surfaces that are not subject to high impact abuse.

HYDROFLOR FLAKE FLOORING SYSTEM

Uses an epoxy topcoat with light blockers in place of polyurethane to qualify as a very low VOC system.

AQUASEAL

A clear water-based epoxy for sealing concrete.

ARCHITECTURAL TERRAZZITE ZV

A polished synthetic Terrazzo-like floor topping using marble/granite type aggregate and polyols based on low emission technology.

SITUCLAD E

A water-based epoxy system incorporating fibreglass reinforcements to form a hygienic, high impact resistant, high gloss wall cladding system for the food/beverage industry.

NUTHANE SB

5-8 mm polyurethane topping that has the advantage of being able to adhere to damp, cool concrete while still being considered as fast curing, without the release of volatile organic compounds.

QUALIDECK SYSTEM, QUALIPUR 252/372

A range of high quality waterproofing systems for internal application. See our product manual on our website for further information.

RAPID SHIELD UV

High performance, cost effective method of sealing and maintaining concrete flooring.

These products comply with ASTM 3960 (contain less than 140 gms/litre of volatile material).

1800 687 627

www.nuplexconstruction.com.au www.nuplexconstruction.co.nz

