EXTRUDED MAXIBLOCK®

The strongest Blockout shutter



The Extruded Blockout Maxiblock® Roller Shutter provides the best security and protection in our range. Our exclusive Maxiblock® security system includes a heavy duty track and special bottom bar along with the stronger extruded slats and Maxiblock's unique side locking chambers. These chambers secure the shutter slats inside the track, making it almost impossible to pull the slats out of position (up to 1500 kgs pulling force).

The extruded shutter profile comes in either nonperforated or with aligned perforations and custom colours are also available on request.



Blockout's Extruded
Maxiblock® is made
from a 40mm double wall
extruded aluminium profile
with a wall thickness
of 1.2mm.

TECHNICAL INFORMATION

Maximum width - 5 metres

Track sizes - 70mm

Colour range - Standard and customised

colours available

Profile - Perforated and non-perforated.

MAXIVIEW® STANDARD

Perforated option will maintain your views



Blockout's Maxiview Standard perforated option achieves external visibility through 54,000 perforations per square metre in the shutter profile. The perforations are only 19% of the overall shutter profile (curtain), therefore glare, heat gain and heat loss are still reduced.

All Maxiview Shutters have a tighter rolling action than conventional shutters, therefore retracting into a smaller pelmet (or headbox).

The perforated version will also maintain daytime privacy while admitting filtered light and ventilation.



Maxiview[®] Standard Shutter is manufactured with a **45mm single** wall extruded aluminium interlocking profile.

TECHNICAL INFORMATION

Maximum width - 5 metres

Track sizes - 63mm

Colour range - Standard and customised

colours available

Profile - Perforated and non-perforated.